20077 15 PEC 64 25X1			The second secon	The second secon	entered to the second of the s
FROM: ACTION: INFO:	ROUTING INT	10 (0) (0) (0) (0)	PRIORIT	16	The second secon
25X1 TOR: \$230 16 DEC 64	OSA 1 - 20		e des condents con a	IN 62839	
25X1 PRIORITY 25X1	MADE FLIGHT 85 ON 15 DEC	64.	one Pri or	Cos TED	25X1 25X1

- TAKE OFF 0825 FOR 1 HOUR AND 2 MINUTES. MISSION: ENGINE SHUT
 DOWN AT 2.0 MACH WITH HYDROGEN IGNITION SYSTEM, ACCELERATION TO 2.8

 MACH. OBTAIN ENGINE CAM DATA. GROSS WEIGHT 109,650 POUNDS, C.G.

 21.3. TAKEOFF DISTANCE 6800 FEET, TAKEOFF SPEED 220 KNOTS, TEMP 17

 DEGREES, WIND CALM. MAXIMUM SPEED 2.84 MACH, MAXIMUM ALTITUDE

 74,500 FEET. TIME OVER 2.0 MACH 25 MINUTES, TIME OVER 2.6 MACH

 12 MINUTES, TIME OVER 2.8 MACH 5 MINUTES. TIME OVER 50,000 FEET

 35 MINUTES.
- 2. ENGINES WERE TRYMMED PRIOR TO TAKE OFF AS FOLLOWS AND WERE NOT RETRIMMED IN FLIGHT. LEFT 745 DEGREES, RIGHT 752 DEGREES.

 ACCELERATION WAS SMOOTH WITH SOME ROUGHNESS NOTED UP TO 2.55

 MACH. AN UNLIMITED CLIMB WAS MADE THROUGH TUNNEL. ROUGH AIR WAS NOTED AT THE HIGHER ALTITUDES. WHILE STRAIGHT AND LEVEL AT 1.4

 TO 1.6 MACH THE ALTITUDE HOLD WAS ENGAGED WITH ADVERSE PITCH

USAF review(s) completed.

SECRE:

GROUP 1 EXPLUSED FROM AUTO-MATIO DOWNGRAPHIC AND DECLASSIFICATION SECPET

25X1

IN 62839

PAGE TWO

REACTION ON THE ARTICLE, WAS DISENGAGED. CIPS WERE VARYING ONE ONE HALF POUNDS DURING ACCELERATION. DURING A LEFT TURN AT 2.8 MACH. 400 KEAS CLIMBING FROM 69,000 FEET TO 74,000 FEET, 1 SHOCK POPPED THEN THE OTHER SPIKES FORWARD CLEARED THE DISTURBANCES. "EGT'S DID NOT GO OVERBOARD DURING STALLS. PILOT NOTED PITCH TRIM INDICATOR 5 DEGREES DOWN DUPING TUPN. COMMENTED C.G. SEEMED AFT. POWER REDUCED TO MILITARY FOR DECELERATION CAM DATA AT 1.5 MACH. ACCELERATION TO 2.8 MACH AT 400 KEAS C.C. APPEARED TO BE AFT DURING ACCELERATION IN ROUGHNESS. FUEL FLOWS WE'RE MATCHED AT 350 KEAS 74,000 FEET, 2.8 MACH WITH NO STALLS. ENGAGED MACH HOLD AT 2.8 MACH PLUS OF MINUS . 02 MACH IN 45 DEGPEE LEFT BANK. BEST OPERATION IN ARTICLE TO DATE. AT 2.0 MACH 375 KEAS PEDUCED POWER DROPPED R ENGINE, AFT BY-PASS OPEN, FORWARD OPEN, SPIKE AUTO. THROTTLE TO ONE HALF BEFORE ENGINE HAD DECELEPATED TO IDLE (5-6) SECOND. ROUGHNESS NOTED. I SHAPP STALL NOTED. POWER TO MILITARY, SPIKE CAM DATA AT 350 KEAS. LANDED.

3. PARACHUTE FAILED. FOLLED OUT ON LAKE BED EXTENSION, BRAKED NORMALLY. PILOT REMARKED PITCH AXIS UNUSUAL DURING FLIGHT.

END OF MESSAGE